PL308



PROPERTY	DESCRIPTION	
Primary/Stalk Yarn Type:	Nylon	
Secondary/Thatch Yarn Type:	N/A	
Yarn Cross Section:	Texturized Nylon	
Standard Color(s)*:	Turf or Verde/Lime	
UV Stabilized:	Yes	
Fabric Construction:	Tufted	
Primary Backing:	ArmorLoc [™] 3L Stabilized Woven PP/PET Multilayer	
Coating Type(s):	Natural Rubber or SilverBack™ Polyurethane	
Perforations:	Not Recommended	
Yarn Denier/Ends:	4400/8	
Pile Height:	3/8"	
Face Weight:	36 oz/yd²	
Fabric Width:	15 ft.	



APPLICATION

As one of our premier putting surfaces, this product is ideal for putting, short chip shots, and indoor golf facilities. The speed of the green will depend on the installation method. This product can be installed indoors or outdoors on concrete or a compacted aggregate base.









PL308

FINISHED FABRIC	ENGLISH	ENGLISH SYSTEM		SYSTEM	ASTM TEST F-1551
Nominal Specification	Value	Units	Value	Units	Method
Pile Height (Nominal)	.375	ln.	9.53	mm.	D-5823
Face Weight	36	oz/yd²	1221	g/m²	D-5848
Total Fabric Weight	71	oz/yd²	2407	g/m²	D-5848
Primary Backing Weight	7	oz/yd²	237	g/m²	D-5848
Secondary Coating Weight	28	oz/yd²	1390	g/m²	D-5848
Tuft Bind	>8	lbs.	>3.6	Kg.	D-1335
Grab Tear Strength (Average)	>200	lbs.	>91	Kg.	D-5034
Lead Content	<50	ppm	<50	ppm	F-2765
Total Yarn Linear Density	4,400	Denier	4,889	D-Tex	D-1577
Tensile Strength	8.0	lbs.	3.63	Kg.	D-5034
Stitch Rate	28	Per 3"	71.12	Per 10 cm	D-5793
Machine Gauge	0.1875	ln.	0.48	Cm.	D-5793
Flammability	TEST	PASSED	TEST	PASSED	D-2859
Fiber Thickness	-	_	100	microns	D-3218



