

PL960

Reinforced with
 **ANTIMICROBIAL**
PROTECTION



APPLICATION

This is an excellent landscape/multipurpose product that offers thatch, which provides added body, reducing the amount of infill needed, and silver ion for antimicrobial and anti-bacterial. The two color blend of this surface provides a truly authentic look and feel that resembles a natural lawn. This product can be used for landscapes, playgrounds, pet areas, fringes, indoor arenas, training facilities and much more. This product can be installed indoors or outdoors on concrete or a compacted aggregate base.

PROPERTY

DESCRIPTION

Primary/Stalk Yarn Type:	Polyethylene
Secondary/Thatch Yarn Type:	Polyethylene
Yarn Cross Section:	Curled Diamond Polyethylene Monofilament with a Texturized Polyethylene Thatch
Standard Color(s)*:	Field/Olive with Field/Jute Thatch
UV Stabilized:	Yes
Fabric Construction:	Tufted
Primary Backing:	ArmorLoc™ 3L Stabilized Woven PP/PET Multilayer
Coating Type(s):	SilverBack™ Polyurethane
Perforations:	Optional
Yarn Denier/Ends:	Stalk: 13000/8 Thatch: 5000/8
Pile Height:	1-5/8"
Face Weight:	78 oz/yd ²
Fabric Width:	15 ft.



 **ArmorLoc™ 3L**



*Custom colors available upon request

200 Howell Dr. Dalton GA 30721


www.cpturf.com

800.564.4492


 **CONTROLLED**
PRODUCTS

PL960

FINISHED FABRIC	ENGLISH SYSTEM		METRIC SYSTEM		ASTM TEST F-1551
Nominal Specification	Value	Units	Value	Units	Method
Pile Height (Nominal)	1.625	In.	41.275	mm.	D-5823
Face Weight	78	oz/yd ²	2645	g/m ²	D-5848
Total Fabric Weight	105	oz/yd ²	3560	g/m ²	D-5848
Primary Backing Weight	7	oz/yd ²	237	g/m ²	D-5848
Secondary Coating Weight	20	oz/yd ²	678	g/m ²	D-5848
Tuft Bind	>8	lbs.	>3.6	Kg.	D-1335
Grab Tear Strength (Average)	>200	lbs.	>91	Kg.	D-5034
Lead Content	<50	ppm	<50	ppm	F-2765
Total Yarn Linear Density	18,000	Denier	19,980	D-Tex	D-1577
Tensile Strength	8	lbs.	3.63	Kg.	D-5034
Stitch Rate	9.5	Per 3"	12.45	Per 10 cm	D-5793
Machine Gauge	.375	In.	.95	Cm.	D-5793
Flammability	TEST	PASSED	TEST	PASSED	D-2859
Water Permeability with Infill, Perforated	>30	In./Hr.	>76	Cm./Hr.	F-1551
Fiber Thickness	-	-	235	microns	D-3218



CURB



EQUIPMENT

It is the policy of Controlled Products to continuously improve their line of products. Therefore, Controlled Products reserves the right to change, modify or discontinue systems, specifications and accessories of all products at any time without notice or obligation to purchaser.