## PL986



PROPERTY	DESCRIPTION
Primary/Stalk Yarn Type:	Polyethylene
Secondary/Thatch Yarn Type:	N/A
Yarn Cross Section:	Texturized Polyethylene
Standard Color(s)*:	Field
UV Stabilized:	Yes
Fabric Construction:	Tufted
Primary Backing:	ArmorLoc <sup>™</sup> 3L Stabilized Woven PP/PET Multilayer
Coating Type(s):	5mm Polyurethane Foam
Perforations:	Not Recommended
Yarn Denier/Ends:	5600/8
Pile Height:	9/16"
Face Weight:	34 oz/yd²
Fabric Width:	15 ft.



## **APPLICATION**

PL986 is a multipurpose synthetic turf with a popular infill-free design. Suitable for both indoor and outdoor applications, it can be installed over concrete or an aggregate base, as well as used as a portable solution. PL986 comes with a 5mm foam pad for added comfort and impact resistance.









## PL986

FINISHED FABRIC	ENGLIS	ENGLISH SYSTEM		SYSTEM	ASTM TEST F-1551
Nominal Specification	Value	Units	Value	Units	Method
Pile Height (Nominal)	.5625	ln.	14.29	mm.	D-5823
Face Weight	34	oz/yd²	1,153	g/m²	D-5848
Total Fabric Weight	119	oz/yd²	4,035	g/m²	D-5848
Primary Backing Weight	7	oz/yd²	237	g/m²	D-5848
Secondary Coating Weight	85	oz/yd²	2,882	g/m²	D-5848
Tuft Bind	>10	lbs.	>4.5	Kg.	D-1335
Grab Tear Strength (Average)	>250	lbs.	>113.4	Kg.	D-5034
Lead Content	<50	ppm	<50	ppm	F-2765
Total Yarn Linear Density	5,600	Denier	6,222	D-Tex	D-1577
Tensile Strength	8	lbs.	3.6	Kg.	D-5034
Stitch Rate	16	Per 3"	21	Per 10 cm	D-5793
Machine Gauge	3/16	ln.	0.5	Cm.	D-5793
Flammability	TEST	PASSED	TEST	PASSED	D-2859
Fiber Thickness	-	-	100	microns	None



