


PL960



Re-enforced with **ChargeGuard**

PROPERTY	DESCRIPTION
Primary/Stalk Yarn Polymer	Polyethylene
Secondary/Thatch Yarn Polymer	Polyethylene
Yarn Cross Section	Texturized Polyethylene
Standard Colors	Field/Olive with Field/Jute Thatch
Coating Type(s)	SilverBack™ Polyurethane
Perforations	Yes
Pile Height	1 9/16"
Total Fabric Weight	105 oz
Fabric Width	15 ft.
Yarn Shape	



KDK



APPLICATION

This is an excellent landscape /multipurpose product that offers thatch, which provides added body, reducing the amount of infill needed, and silver ion for antimicrobial and anti-bacterial. The two color blend of this surface provides a truly authentic look and feel that resembles a natural lawn. This product can be used for landscapes, playgrounds, pet areas, fringes, indoor arenas, training facilities and much more. This product can be installed indoors or outdoors on concrete or a compacted aggregate base.



*Custom colors available upon request

200 Howell Dr. Dalton GA 30721

www.cpturf.com

800.564.4492




CONTROLLED
PRODUCTS




PL960

FINISHED FABRIC	ENGLISH SYSTEM		METRIC SYSTEM		ASTM TEST F-1551
Nominal Specification	Value	Units	Value	Units	Method
Pile Height (Nominal)	1.563	In.	39.7	mm.	D-5823
Face Weight	78	oz/yd ²	2645	g/m ²	D-5848
Total Fabric Weight	105	oz/yd ²	3560	g/m ²	D-5848
Primary Backing Weight	7.4	oz/yd ²	251	g/m ²	D-5848
Secondary Coating Weight	20	oz/yd ²	678	g/m ²	D-5848
Tuft Bind	>8	lbs.	>3.6	Kg.	D-1335
Grab Tear Strength (Average)	>200	lbs.	>91	Kg.	D-5034
Lead Content	<50	ppm	<50	ppm	F-2765
Total Yarn Linear Density	18,000	Denier	19,980	D-Tex	D-1577
Tensile Strength	8	lbs.	3.63	Kg.	D-5034
Stitch Rate	9.5	Per 3"	12.45	Per 10 cm	D-5793
Machine Gauge	.375	In.	.95	Cm.	D-5793
Flammability	TEST	PASSED	TEST	PASSED	D-2859
Water Permeability w/Infill	>30	In./Hr.	>76	Cm./Hr.	F-1551
Fiber Thickness	22	mils	235	microns	D-3218
Fabric Width	15	Ft.	4.6	M	None



CURB



EQUIPMENT