
## PL958



PROPERTY	DESCRIPTION		
Primary/Stalk Yarn Polymer	er Polyethylene		
Secondary/Thatch Yarn Polymer	Polyethylene		
Yarn Cross Section	Polyethylene Monofilament; Texturized Polyethylene		
Standard Colors	Field/Olive; Field/Clover		
Coating Type(s)	SilverBack™ Polyurethane		
Perforations	Yes		
Pile Height	1 3/4"		
Total Fabric Weight	102 oz		
Fabric Width	15 ft.		



## **APPLICATION**

This is an excellent landscape /multipurpose product that offers thatch, which provides added body, reducing the amount of infill needed. The two color blend of this surface provides a truly authentic look and feel that resembles a natural lawn. This product can be used for landscapes, playgrounds, pet fringes, indoor arenas, training facilities and much more. This product can be installed indoors or outdoors on concrete or a compacted aggregate base.









## **TESTING**

## **PL958**

FINISHED FABRIC	ENGLISI	H SYSTEM	METRIC	SYSTEM	ASTM TEST F-1551
Nominal Specification	Value	Units	Value	Units	Method
Pile Height (Nominal)	1.75	In.	44.45	mm.	D-5823
Face Weight	75	oz/yd²	2543	g/m²	D-5848
Total Fabric Weight	102	oz/yd²	3458	g/m²	D-5848
Primary Backing Weight	7.4	oz/yd²	251	g/m²	D-5848
Secondary Coating Weight	20	oz/yd²	678	g/m²	D-5848
Tuft Bind	>8	lbs.	>3.6	Kg.	D-5848
Grab Tear Strength (Average)	>200	lbs.	>91	Kg.	D-5848
Lead Content	<50	ppm	<50	ppm	D-1335
Total Yarn Linear Density	10,400	Denier	17,553	D-Tex	D-5034
Tensile Strength	8	lbs.	3.63	Kg.	F-2765
Stitch Rate	11.5	Per 3"	15.1	Per 10 cm	D-1577
Machine Gauge	.25	ln.	.96	Cm.	D-5793
Flammability	TEST	PASSED	TEST	PASSED	D-5793
Water Permeability w/Infill	>30	In./Hr.	>76	Cm./Hr.	D-2859
Fiber Thickness	22	mils	235	microns	F-1551
Fabric Width	15	Ft.	4.6	М	None

